

LENS COMPARISON CHART

	DC1	UH480	FVX200	F200SYS	A200SYS
Optimum distance to screen	14.5 ft to 17.5 ft	14.5 ft to 17.5 ft	14 ft to 25 ft	14 ft to 25 ft	14 ft to 25 ft
Allowable distance to screen	12 ft to 20 ft	12 ft to 20 ft	14 ft to 28 ft	14 ft to 28 ft	14 ft to 28 ft
Minimum throw distance	1.6 times native 16:9 image width -OR- 2.85 times screen height	1.6 times native 16:9 image width -OR- 2.85 times screen height	1.8 times 2.40:1 screen width -OR- 4.3 times screen height	1.8 times 2.40:1 screen width -OR- 4.3 times screen height	1.8 times 16:9 screen width -OR- 3.2 times screen height
Use with curved screen?	Yes	Yes	No	No	No
Use with 2.35:1 or 2.40:1 screen?	Yes	Yes	Yes	Yes	No
Use with 16:9 screen?	No	No	No	No	Yes
<i>Accessories</i>					
Conversion kit for longer distances	Yes	Yes	No	No	No
Attachment types	Automated or Manual Sleds or Fixed	Automated or Manual Sleds or Fixed	Fixed Bracket	Fixed Bracket	Automated Sled
Projector mounting hardware available?	Yes	Yes	No	Yes	Yes

