



# Sony FVX200S

## Anamorphic Lens System

For Sony Projector models:

VPL-VW85; VPL-VW90

### Installation

- The FVX200S bracket installs between the projector and projector mount. A black metal spacer is included to ensure the bracket and projector mount are level. Place the lens bracket on top of the two front attachment posts and spacer over the back-most mount location (see your projector's manual for appropriate attachment locations). Place the projector mount on top of the lens bracket and spacer, insert the projector mount screws, and tighten securely.
- Before installing the lens, make sure the projector lens is horizontally aligned with the center line of the screen and that the image is not tilted left to right relative to the top and bottom of the screen border. Make sure the projector ceiling mount is secure since the anamorphic lens system will add mass to the front of the projector.
- Place the lens between the two slotted "forks" on the bracket and insert one #10-32x3/8 lens mounting screw and brass washer into each side of the lens and tighten (do not tighten the screws fully yet). The lens is properly oriented with the "Panamorph" logo on the bottom.
- Install the lens system by placing the slot openings over the mounting screws and sliding it back until the bracket stops. Tighten the lens mounting screws.
- Turn on the projector. REMOVE THE PROTECTIVE FILM ON THE FRONT OF THE FVX200 LENS. Using the remote, select "Lens => Zoom" and adjust the image size to fill the entire width of screen (refer to the fine tuning instructions included with the lens for final setup). Select "Lens => Focus" and tune in the focus.

### PROJECTOR SETTINGS WHEN USING THE FVX200S

For 2.35:1 or greater aspect ratio sources:

- From the remote, use the **Wide Mode Button > Anamorphic Zoom** AND **Menu > Input > Aspect=16:9**.

For smaller format sources such as 1.85:1, 16:9 or 4:3 aspect ratios

- From the remote, use the **Wide Mode Button > Normal** OR **Menu > Input > Aspect=4:3**.

Contents:

One FVX200S Lens Attachment Bracket

Two (2) #10-32x3/8 Black Lens mounting screws and brass washers

One (1) Black Metal Spacer